Overview

HP 255 G10 Notebook PC



Left

- 1. Internal Dual Digital Microphone (2)
- 2. Webcam
- 3. Camera Shutter
- 4. Webcam LED
- 5 Clickpad

- 6. Audio Combo Jack
- 7. SuperSpeed USB Type-C[®] 5Gbps signaling rate1 (Supports data transfer only and does not support charging or external monitors)
- 8. HDMI Port (Cable Sold Separately)
- **9.** SuperSpeed USB Type-A 5Gbps signaling rate1 port (USB 3.2 Gen 1)



Overview



Right

- 1. Power Button
- 2. Power Connector

- 3. SuperSpeed USB Type-A 5Gbps signaling rate1 port (USB 3.2 Gen 1)
- 4. Fingerprint Reader (Select Models)



Overview

At a Glance

- Preinstalled with Windows 11 Pro, Windows Home or FreeDOS
- Choice of AMD Ryzen[™] APU processors
- Choice of 39.62 cm (15.6") diagonal HD and Ultra Wide Viewing Angle FHD 300 nit displayOptimize your video calls with an FHD camera(optional) and temporal noise reduction that adjusts the lighting to your environment.
- Fast dual channel DDR4 SODIMM memory up to 16 GB
- Enhanced security features including discrete TPM 2.0 for BCL-R, Firmware TPM for MDN and optional Fingerprint reader.
- Weight with basic configurations starting at 3.3lb/1.52kg
- Support wireless options for connectivity on the go including gigabit-speed up to Wi-Fi[®] 6
- Supports fast charging (50% in 45 minutes) with no impact on battery recharge cycles
- Full size, optional backlit keyboard and spill resistant, clickpad with Precision Touchpad Supported certified
- Camera shutter door to ensure privacy
- Undergoes MIL-STD 810H tests¹

1. MIL-STD 810H is not intended to demonstrate fitness of U.S. Department of Defense contract requirements or for military use. Test results are not a guarantee of future performance under these test conditions. Accidental damage requires an optional HP Accidental Damage Protection Care Pack.

NOTE: See important legal disclosures for all listed specs in their respective features sections.



PRODUCT NAME

HP 255 G10 Notebook PC

OPERATING SYSTEMS

Preinstalled

Windows 11 Pro¹ Windows 11 Pro Education¹ Windows 11 Home – HP recommends Windows 11 Pro for business¹ Windows 11 Home Single Language – HP recommends Windows 11 Pro for business¹ Windows 11 Home Education – HP recommends Windows 11 Pro for business¹ FreeDOS

1. Not all features are available in all editions or versions of Windows. Systems may require upgraded and/or separately purchased hardware, drivers, software or BIOS update to take full advantage of Windows functionality. Windows is automatically updated and enabled. High speed internet and Microsoft account required. ISP fees may apply and additional requirements may apply over time for updates. See http://www.windows.com.

Processor ^{3,4,5}	Cores	Threads	L3 Cache	Max Boost Frequency 5	Base Frequency
AMD Ryzen™ 7-7730U	8	16	16MB	4.50GHz	2.00GHz
AMD Ryzen™ 5-7530U	6	12	16MB	4.50GHz	2.00GHz
AMD Ryzen™ 5-7520U	4	8	4MB	4.3GHz	2.8GHz
AMD Ryzen™ 3-7330U	4	8	8MB	4.30GHz	2.30GHz
AMD Ryzen™ 3-7320U	4	8	4MB	4.1 GHz	2.4GHz
AMD Athlon™ Silver 7120U	2	2	2MB	3.5GHz	2.4GHz

PROCESSORS

Multicore is designed to improve performance of certain software products. Not all customers or software applications will necessarily benefit from use of this technology. Performance and clock frequency will vary depending on application workload and your hardware and software configurations. AMD's numbering is not a measurement of clock speed.
 Processor speed denotes maximum performance mode; processors will run at lower speeds in battery optimization mode.

AMD Max Boost frequency performance varies depending on hardware, software and overall system configuration.
 In accordance with Microsoft's support policy, HP does not support the Windows 8 or Windows 7 operating system on products configured with Intel and AMD 7th generation and forward processors or provide any Windows 8 or Windows 7 drivers on http://www.support.hp.com

CHIPSET

Chipset is integrated with processor



GRAPHICS

Integrated

AMD Radeon™ Graphics

Supports

Support HD decode, DX12, HDMI 1.4b⁷

7. HD content required to view HD images.

DISPLAY

Non-Touch

39.6 cm (15.6") diagonal, FHD (1920 x 1080), Low Blue Light, IPS, anti-glare, UWVA, micro-edge, 300 nits, sRGB 100% eDP 1.4+PSR2 ^{7,8,9}

39.6 cm (15.6") diagonal, FHD (1920 x 1080), IPS, anti-glare, SVA, micro-edge, 250 nits, 45% NTSC eDP 1.2 ^{7,8,9} 39.6 cm (15.6") diagonal, FHD (1920 x 1080), IPS, anti-glare, UWVA, micro-edge, 250 nits, 45% NTSC eDP 1.2 ^{7,8,9} 39.6 cm (15.6") diagonal, HD (1366x768), IPS, anti-glare, SVA, micro-edge, 250 nits, 45% NTSC eDP 1.2 ^{7,8,9}

HDMI

Port supports resolutions up to 1920 x 1200 external resolution @60 Hz

Display Size (Diagonal)

15.6" 39.6 cm (15.6")

7. HD content required to view HD images.

8. Sold separately or as an optional feature.

9. Resolutions are dependent upon monitor capability, and resolution and color depth settings.

STORAGE AND DRIVES

Primary M.2 Storage

1 TB PCIe[®] NVMe[™] M.2 SSD ¹⁰ 1 TB PCIe[®] Gen4x4 NVMe[™] M.2 SSD TLC ^{10,11} 512 GB PCIe[®] NVMe[™] M.2 QLC Solid State Drive ¹⁰ 256 GB PCIe[®] NVMe[™] M.2 QLC Solid State Drive ¹⁰ 128 GB PCIe[®] NVMe[™] TLC Solid State Drive¹⁰

10. For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.
11. Available only to HK (Hong Kong), TW(Taiwan) and CN (China).



MEMORY

Maximum Memory 16 GB DDR4-3200 MT/s SDRAM ^{12,13}

Memory

16 GB DDR4-3200 MT/s SDRAM (1 x 16 GB) ^{12,13} 16 GB DDR4-3200 MT/s SDRAM (2 x 8 GB) ^{12,13} 8 GB DDR4-3200 MT/s SDRAM (1 x 8 GB) ^{12,13} 8 GB DDR4-3200 MT/s SDRAM (2 x 4 GB) ^{12,13} 8GB LPDDR5-5500 MT/s (onboard) ^{12,13} 4 GB DDR4-3200 MT/s SDRAM (1 x 4 GB) ^{12,13} 4GB LPDDR5-5500 MT/s (onboard) ^{12,13}

Memory Slots

2 SODIMM (BCL-R only) ^{12,13} Support Dual Channel Memory

12. All slots are non-accessible / non-upgradeable.

13. Due to the non-industry standard nature of some third-party memory modules, we recommend HP branded memory to ensure compatibility. If you mix memory speeds, the system will perform at the lower memory speed.

NETWORKING/COMMUNICATIONS

WLAN

Realtek 8852BE-VS (1X1) Wi-Fi[®] 6 Bluetooth[®] 5.3 WLAN Wireless Card ¹⁴ Realtek 8852BE (2X2) Wi-Fi[®] 6 Bluetooth[®] 5.3 WW WLAN Wireless Card ¹⁴

Miracast

Compatible with Miracast-certified devices (For Win11)¹⁵

14. Wireless access point and internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 is backwards compatible with prior 802.11 specs.
 15. Miracast is a wireless technology your PC can use to project your screen to TVs, projectors, and streaming.



AUDIO/MULTIMEDIA

Audio

2 Integrated stereo speakers Integrated Microphone

Camera

720p HD camera with Temporal Noise Reduction ⁷ 1080p FHD camera with Temporal Noise Reduction ⁷

7. HD content required to view HD images.

KEYBOARDS/POINTING DEVICES/BUTTONS & FUNCTION KEYS

Keyboard

Full Size Textured island-style Keyboard and optional Backlit and spill resistant ¹⁶

Pointing Device

Touchpad with multi-touch gesture support (PTP certified)

Function Keys

ESC: system information F1 - Open " How to get help in Windows 11" webpage F2 - Brightness Down F3 - Brightness Up F4 - Display Switching F5 - Blank F6 - Mute F7 - Volume Down F8 -Volume Up F9 - Previous F10 - Play/Pause F11 - Next F12 - Airplane mode

16. Backlit keyboard is an optional feature.



SOFTWARE AND SECURITY

Software

HP Smart Health ¹⁷ ENERGY STAR® UWP (Universal Windows Platform for Windows) Express VPN Microsoft Office (Microsoft office sold separately. Internet access required for activation) WPS Office Dropbox Promotion ¹⁸ HP QuickDrop¹⁹ E-QR Code sMedio True DVD for HP

Manageability Features

HP SSRM (HP Support Sent Recovery Media) ²⁰ Windows Push Button Reset Recovery ²¹

Security Management

McAfee LiveSafe^{™ 22}

17. HP Smart Health requires HP TechPulse, a telemetry and analytics platform that provides critical data around devices and applications and is not sold as a standalone service. HP TechPulse follows stringent GDPR privacy regulations and is ISO27001, ISO27701, ISO27017 and SOC2 Type2 certified for Information Security. Internet access with connection to TechPulse portal is required. For full system requirements, please visit http://www.hpdaas.com/requirements. Purchase of any HP TechPulse-enabled service necessitates enabling software to run on each device. HP Services Scan is provided thru Windows Update and will check entitlement on each hardware device to determine if an HP TechPulse-enabled service has been purchased, and will download applicable software automatically. To disable this feature, please follow the instructions at http://www.hpdaas.com/requirements.

18. 100 GB of free Dropbox storage for 12 months from date of registration. For complete details and terms of use, including cancellation policies, visit the Dropbox website at https://www.dropbox.com/help/space/hp-promotion . Internet service required and not included.

19. HP Quick Drop requires Internet access and Windows 10 and higher PC preinstalled with HP QuickDrop app and either an Android device (phone or tablet) running Android 7 or higher with the Android HP QuickDrop app, and /or an iOS device (phone or tablet) running iOS 12 or higher with the iOS HP QuickDrop app.

20. Sold separately or as an optional feature.

21. Must activate within 180 days of Windows activation.

22. 30-day McAfee® LiveSafe™ trial included. Internet access required and not included. Subscription required after expiration. See http://www.McAfee.com for more details.



Technical Specifications

POWER

Power Supply

HP Smart 65 W EM External AC power adapter²³ HP Smart 45 W External AC power adapter²³

Battery

HP Long Life 3-cell, 41 Wh Li-ion Polymer ^{24,25}

Power Cord 1M (3.28 feet) length power cord

Battery Life

Up to 12 hours and 1 minutes with 41 whr battery(HP Long Life 3-Cell, 41 Whr Polymaer, UMA graphic, AMD MDN, display set to 200 nits, 2*4G memory, 256 GB SSD)²⁶

Battery Weight

1.85 lb 0.407 kg

23. Availability may vary by country.

24. Battery is internal and not replaceable by customer. Serviceable by warranty.

25. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors.

26. MM18 battery life will vary depending on various factors including product model, configuration, loaded applications, features, use, wireless functionality, and power management settings. The maximum capacity of the battery will naturally decrease with time and usage. See www.bapco.com for additional details.

WEIGHTS & DIMENSIONS

Product Weight

Starting at 3.3 lb ²⁷ Starting at 1.52 kg²⁷

Product Dimensions (W x D x H)

14.17 x 9.29 x 0.73 in 36 x 23.6 x 1.86 cm

Packaging Dimensions (W x D x H) ²⁸

12-15" boxes (305mm height): 1200mm x 1000mm x 1080mm

27. Weight will vary by configuration. Does not include power adapter.

28. Product packaging size varies based on options chosen. Please contact your HP representative for your packaging size details. For detailed packaging information, access the HP Commercial Notebooks Packaging Guide.



PORTS/SLOTS

2 SuperSpeed USB Type-A 5Gbps signaling rate

1 SuperSpeed USB Type-C[®] 5Gbps signaling rate (Supports data transfer only and does not support charging or external monitors)

1 HDMI v1.4b ²⁹

1 AC Power

1 Headphone/microphone combo jack

29. HDMI cable sold separately

SERVICE AND SUPPORT

1-year limited warranties and 90 day software limited warranty options depending on country. Batteries have a default one year limited warranty. Refer to http://www.hp.com/support/batterywarranty/ for additional battery information. On-site service and extended coverage is also available. HP Care Pack Services are optional extended service contracts that go beyond the standard limited warranties. To choose the right level of service for your HP product, use the HP Care Pack Services Lookup Tool at: http://www.hp.com/go/cpc.³⁰

30. HP Care Packs are sold separately. Service levels and response ties for HP Care Packs may vary depending on your geographic location. Service starts on date of hardware purchase. Restrictions and limitations apply. For details, visit www.hp.com/go/cpc. HP services are governed by the applicable HP terms and conditions of service provided or indicated to Customer at the time of purchase. Customer may have additional statutory rights according to applicable local laws, and such rights are not in any way affected by the HP terms and conditions of service or the HP Limited Warranty provided with your HP Product.



SYSTEM UNIT

Stand-Alone Power Requirements (AC Power)	
Nominal Operating Voltage Average Operating Power	19.5V 3.73W (Local video playback)
Integrated graphics	Yes
Discrete Graphics	N/A
Max Operating Power	UMA < 45W
Temperature	
Operating	32° to 95° F (0° to 35° C) (not writing optical) 41° to 95° F (5° to 35° C) (writing optical)
Non-operating	-4° to 140° F (-20° to 60° C)
Relative Humidity	
Operating	10% to 90%, non-condensing
Non-operating	5% to 95%
Shock	
Operating	40 G, 2 ms, half-sine
Non-operating	200 G, 2 ms, half-sine
Random Vibration	
Operating	1.043 grams
Non-operating	3.5 grams
Altitude (unpressurized)	
Operating	-50 to 10,000 ft (-15.24 to 3,048 m)
Non-operating	-50 to 40,000 ft (-15.24 to 12,192 m)
Planned Industry Standard	
Certifications Regulatory Model Number	TPN-Q287
CSA/UL 62368-1	Yes
ENERGY STAR®	Certified ³¹
EPEAT®	EPEAT® Gold in the United States ³²
FCC/ICES/CISPR/VCCI	Yes
CE MARKING	Yes
GS Mark	Yes
Related commodity should comply wit	h ISO 9241 Standards.
China CCC/SRRC	Yes
Taiwan BSMI/NCC	Yes
Korea KCC/KC/KES	Yes
Ukraine NSoC/TEC	Yes
EAEU Compliance	Yes
Saudi Arabian Compliance	Yes
тсо	Νο
WW RoHS	Yes
Low Blue Light	Yes

31. Configurations of the HP 255 G10 Notebook PC that are ENERGY STAR[®] qualified are identified as HP 255 G10 Notebook PC ENERGY STAR on HP websites and on http://www.energystar.gov.



32. Based on US EPEAT® registration according to IEEE 1680.1-2018 EPEAT®. EPEAT® status varies by country. Visit http://www.epeat.net for more information.

DISPLAYS

1. Actual brightness will be lower with touchscreen or HP Sure View.

NOTE: All specifications represent the typical specifications provided by HP's component manufacturers; actual performance may vary either higher or lower.

15.6 in FHD (1920 x 1080) **Anti-Glare UWVA Low Blue** Light sRGB NWBZ 300 eDP 1.4+PSR2 100 flat LCD Panel

Outline Dimensions (W x H x D)	350.960 x 215.840 max.
Active Area	344.160 x 193.590 typ.
Weight	310g max.
Diagonal Size	15.6 inch
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	1000:1 typ
Refresh Rate	60Hz
Brightness	300 nits ¹
Pixel Resolution - Format	1920 x 1080 (FHD)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	sRGB 100%
Color Depth	8
Viewing Angle	UWVA 89 / 89 / 89 / 89
Low Blue Light	Yes
Power Consumption (W, EBL@ 150nits max/ 200nits max)	2.69 (max) / 3.4 (max)

Panel LCD 15.6-in FHD (1920x1080) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR **NWBZ ultraslim**

Outline Dimensions (W x H)	350.960 x 216.750 max
Active Area	344.160 x 193.590 typ.
Weight	360g max
Diagonal Size	15.6 inch
Surface Treatment	Anti-Glare
Touch Enabled	No
Contrast Ratio	300:1 (typ)
Refresh Rate	60Hz
Brightness	250 nits ¹
Pixel Resolution - Format	1920 x 1080 (FHD)
Backlight	WLED
Pixel Resolution	RGB
Color Gamut Coverage	NTSC 45%
Color Depth	6



Technical Specifications

WLED UWVA 45percent cg Veight 370g max 250nits eDP 1.2 w/o PSR Diagonal Size 15.6 inch NWBZ stim Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 600:1 typ Refresh Rate 60Hz Brightness 250nits 1 Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution RGB Color Gamut Coverage NTSC 45% Color Color Depth 6 Viewing Angle UWVA 85/85/85/85 Low Blue Light No Power Consumption (W, EBL@ 2.88 max / 3.54 max Yaborts max/ 200nits max/ 351.030 x 216.750 max Active Area 344.230 x 193.540 typ WLED SVA 45spercent cg Veight 370g max 150 max Yaborts eDP 1.2 w/o PSR Veight 370g max 150 max	rechnical Specific		
Power Consumption (W, EBL@ 150nits max/ 200nits max) 2.67 max / 3.33 max Panel LCD 15.6-in FHD (1920x1080) Anti-Glare WLED UWVA 45percent 250nits eDT 1.2 w/o PSR NWBZ slim Outline Dimensions (W x H) Active Area 350.960 x 216.750 max. Active Area WLED UWVA 45percent 250nits eDT 1.2 w/o PSR NWBZ slim Outline Dimensions (W x H) Active Area 350.960 x 216.750 max. Active Area WLED UWVA 45percent 250nits eDT 1.2 w/o PSR NWBZ slim Outline Dimensions (W x H) Backleft 350.960 x 216.750 max. Active Area WLED UWVA 45percent 250nits eDT 1.2 w/o PSR NWBZ slim Outline Dimensions (W x H) Backleft 350.960 x 216.750 max. Panel LCD 15.6-in HD (1366x769) Anti-Glare WLED VIED Spectra 250nits eDT 1.2 w/o PSR NWBZ ultraslim Outline Dimensions (W x H) Backleft 351.030 x 216.750 max Panel LCD 15.6-in HD (1366x769) Anti-Glare WLED X4 45percent Glare WLED X4 45percent		Viewing Angle	SVA 45/45/15/30
Panel LCD 15.6-in FHD (1920x1080) Anti-Glare WLED UWVA 45percent of ZSOnits eDP 1.2 w/o PSR NWBZ slim Outline Dimensions (W x H) Active Area 350.960 x 216.750 max. Active Area 344.160 x 193.590 typ. Wieght 370g max Diagonal Size 15.6 inch Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 600Hz Brightness 250nits 1 Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution RGB Color Gamut Coverage Color Gamut Coverage NTSC 45% Color Depth 6 Viewing Angle UWVA 85/85/85/85 Low Blue Light No Power Consumption (W, EBL@) 2.88 max / 3.54 max 250nits eDF 1, z w/o PSR You gamax Color Gamut Coverage 151.030 x 216.750 max (1365x768) Anti-Glare Yeight 351.030 x 216.750 max MUED VA 459percent og Viegh		Low Blue Light	No
(1920x1080) Anti-Glar WLED JUWVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ slimActive Area344.160 x 193.590 typ.NWBZ slimGagonal Size370 g maxNWBZ slimDiagonal Size5.6 inchNUBE SlimSurface TreatmentAnti-GlareTouch EnabledNo6014Refresh Rate60HzBrighness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDViewing AngleColor DepthColor Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@ 250nits max/ 200nits max)S1.030 x 216.750 maxVIED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimS1.030 and 216.750 maxNWBZ ultraslimSurface Treatment35.6 inchNWBZ ultraslimSurface TreatmentNWBZ ultraslimSurface TreatmentSurface TreatmentNoConcrat RatioNoSurface TreatmentS1.6 inchSurface TreatmentNoSurface Tre			2.67 max / 3.33 max
(1920x1080) Anti-Glar WLED JUWVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ slimActive Area344.160 x 193.590 typ.NWBZ slimGagonal Size370 g maxNWBZ slimDiagonal Size5.6 inchNUBE SlimSurface TreatmentAnti-GlareTouch EnabledNo6014Refresh Rate60HzBrighness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDViewing AngleColor DepthColor Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@ 250nits max/ 200nits max)S1.030 x 216.750 maxVIED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimS1.030 and 216.750 maxNWBZ ultraslimSurface Treatment35.6 inchNWBZ ultraslimSurface TreatmentNWBZ ultraslimSurface TreatmentSurface TreatmentNoConcrat RatioNoSurface TreatmentS1.6 inchSurface TreatmentNoSurface Tre	Panel I CD 15 6-in FHD	Outline Dimensions (W x H)	350 960 x 216 750 max
WLED UWVA 4Spercent cg 370g max 250nits eDP 1.2 w/o PSR Veight 370g max NWBZ slim Veight 370g max NWBZ slim Veight 370g max NWBZ slim Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio Contrast Ratio 600:1 typ Refresh Rate 60Hz Brightness 250nits 1 Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution RGB Color Gamut Coverage NTSC 45% Color Depth 6 Viewing Angle UWVA 85/85/85/85 Low Blue Light No Power Consumption (W, EBL@ 2.88 max / 3.54 max 150nits max/ 200nits max/ 370g max VLED SVA 45percent cg Weight 370g max VMBZ uttrastim No Scinch NWBZ uttrastim Weight 370g max Diagonal Size 15.6 inch Surface Treatment Anti-Glare NWBZ uttrastim Surface Treatment Anti-Glare <td< td=""><td>(1920x1080) Anti-Glare</td><td></td><td></td></td<>	(1920x1080) Anti-Glare		
250nits eDP 1.2 w/o PSR NWBZ stim Diagonal Size 15.6 inch NWBZ stim Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 600:1 typ Refresh Rate 60Hz Brightness 250nits 1 Pixel Resolution - Format 1920 x 1080 (FHD) Backlight WLED Pixel Resolution RGB Color Gamut Coverage NTSC 45% Color Depth 6 Viewing Angle UWVA 85/85/85/85 Low Blue Light No Power Consumption (W, EBL@ 2.88 max / 3.54 max 150nits max/ 200nits max) 351.030 x 216.750 max Panel LCD 15.6-in HD Outline Dimensions (W x H) 351.030 x 216.750 max (1366x768) Anti-Glare Weight 370g max WBZ ultraslim Surface Treatment Anti-Glare NWBZ ultraslim Surface Treatment Anti-Glare NWBZ ultraslim Surface Treatment Anti-Glare Contrast Ratio 300:1 typ Refresh Rate 60Hz	WLED UWVA 45percent cg		
Surface TreatmentAnti-GlareTouch EnabledNoContrast Ratio600:1 typRefresh Rate60HzBrightness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Gamut CoverageUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@2.88 max / 3.54 max1350nts max/ 200nits max)250.152 (ST)Panel LCD 15.6-in HDOutline Dimensions (W x H)Aftive Area344.230 x 193.540 typWIEZ SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ uttraslimOutline Dimensions (W x H)Active Area344.230 x 193.540 typWIEZ SVA 45percent cg 250nits eDP 1.2 w/o PSR NUBZ uttraslimSinface TreatmentActive Area300:1 typRefresh Rate60Hz	-	-	-
Former LCD 15.6-in HD (1366x768) Anti-GlareOutline Dimensions (W x H)NoPanel LCD 15.6-in HD (1366x768) Anti-Glare NMBZ ultraslimOutline Dimensions (W x H)S1.030 x 216.750 max Active AreaAdditional Size Sumfar Canada Size Contrast RatioS1.030 x 216.750 max Active AreaAdditional Size Contrast RatioS1.030 x 216.750 max Active AreaMark Bis Contrast Ratio Contrast RatioS1.030 x 216.750 max Active AreaAdditional Size Contrast RatioS1.030 x 216.750 max Active AreaMBZ ultraslimS1.030 x 216.750 max <br< td=""><td>NWBZ SUM</td><td>-</td><td></td></br<>	NWBZ SUM	-	
Refresh Rate60HzBrightness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@2.88 max / 3.54 max150nits max/ 200nits max)351.030 x 216.750 maxActive Area344.230 x 193.540 typWLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimDutline Dimensions (W x H)Signal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate6Hz		Touch Enabled	
Refresh Rate60HzBrightness250nits 1Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNT5C 45%Color Depth6Viewing AngleUWVA 85/85/855Low Blue LightNoPower Consumption (W, EBL@2.88 max / 3.54 max150nits max/ 200nits max)351.030 x 216.750 maxWIED SVA 45percent cg344.230 x 193.540 typWieght370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60Hz		Contrast Ratio	600:1 typ
Pixel Resolution - Format1920 x 1080 (FHD)BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85/85Low Blue LightNoPower Consumption (W, EBL@)2.88 max / 3.54 max150nits max/ 200nits max)351.030 x 216.750 max(1366x768) Anti-GlareActive AreaWLED SVA 45percent cgWeight351.030 x 216.750 maxNWBZ ultraslimUutline Dimensions (W x H)351.030 x 216.750 maxSufface Treatment15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate6Hz		Refresh Rate	
BacklightWLEDPixel ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimOutline Dimensions (W x H)Sti.030 x 216.750 max370g maxDiagonal Size15.6 inchSurface Treatment Touch EnabledAnti-GlareNoContrast Ratio300:1 typRefresh Rate60Hz		Brightness	250nits ¹
Pixe ResolutionRGBColor Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimOutline Dimensions (W x H)351.030 x 216.750 maxActive Area344.230 x 193.540 typWBZ ultraslimVieight370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60Hz		Pixel Resolution - Format	1920 x 1080 (FHD)
Color Gamut CoverageNTSC 45%Color Depth6Viewing AngleUWVA 85/85/85Low Blue LightNoPower Consumption (W, EBL@2.88 max / 3.54 max150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HDOutline Dimensions (W x H)351.030 x 216.750 max(1366x768) Anti-GlareActive Area344.230 x 193.540 typWLED SVA 45percent cgWeight370g max250nits eDP 1.2 w/o PSR NWBZ ultraslimDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60Hz		Backlight	WLED
Color Depth6Viewing AngleUWVA 85/85/85Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimOutline Dimensions (W x H)351.030 x 216.750 maxVieght370g maxJoigonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60Hz		Pixel Resolution	RGB
Viewing AngleUWVA 85/85/85Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimOutline Dimensions (W x H)351.030 x 216.750 maxActive Area344.230 x 193.540 typWIED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimOutline Dimensions (W x H)351.030 x 216.750 maxSurface Treatment344.230 x 193.540 typDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60Hz		Color Gamut Coverage	NTSC 45%
Low Blue LightNoPower Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimOutline Dimensions (W x H)351.030 x 216.750 maxVueight344.230 x 193.540 typWBZ ultraslimWeight370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60Hz		Color Depth	6
Power Consumption (W, EBL@ 150nits max/ 200nits max)2.88 max / 3.54 maxPanel LCD 15.6-in HD (1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimOutline Dimensions (W x H)351.030 x 216.750 maxActive Area Weight344.230 x 193.540 typWeight Diagonal Size370g maxSurface Treatment Touch EnabledAnti-GlareNoContrast Ratio300:1 typRefresh Rate60Hz		Viewing Angle	UWVA 85/85/85/85
Panel LCD 15.6-in HD Outline Dimensions (W x H) 351.030 x 216.750 max (1366x768) Anti-Glare Active Area 344.230 x 193.540 typ WLED SVA 45percent cg Weight 370g max 250nits eDP 1.2 w/o PSR Diagonal Size 15.6 inch NWBZ ultraslim Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio Refresh Rate 60Hz 60Hz		Low Blue Light	No
(1366x768) Anti-Glare WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslimActive Area344.230 x 193.540 typDiagonal Size370g maxDiagonal Size15.6 inchSurface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60Hz			2.88 max / 3.54 max
WLED SVA 45percent cg Weight 370g max 250nits eDP 1.2 w/o PSR Diagonal Size 15.6 inch NWBZ ultraslim Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 300:1 typ Refresh Rate 60Hz	Panel LCD 15.6-in HD	Outline Dimensions (W x H)	351.030 x 216.750 max
WLED SVA 45percent cg Weight 370g max 250nits eDP 1.2 w/o PSR Diagonal Size 15.6 inch NWBZ ultraslim Surface Treatment Anti-Glare Touch Enabled No Contrast Ratio 300:1 typ Refresh Rate 60Hz	(1366x768) Anti-Glare	Active Area	344.230 x 193.540 typ
250nits eDP 1.2 w/o PSR Diagonal Size 15.6 inch NWBZ ultraslim Diagonal Size Anti-Glare Touch Enabled No Contrast Ratio 300:1 typ Refresh Rate 60Hz	WLED SVA 45percent cg 250nits eDP 1.2 w/o PSR NWBZ ultraslim		
Surface TreatmentAnti-GlareTouch EnabledNoContrast Ratio300:1 typRefresh Rate60Hz		Diagonal Size	15.6 inch
Contrast Ratio300:1 typRefresh Rate60Hz		Surface Treatment	Anti-Glare
Refresh Rate 60Hz		Touch Enabled	No
		Contrast Ratio	300:1 typ
Brightness 250nits ¹		Refresh Rate	60Hz
		Brightness	250nits ¹

6

1366 x 768 (HD)

SVA 45/45/15/30

WLED RGB

NTSC 45%

Pixel Resolution - Format

Backlight

Color Depth

Viewing Angle

Pixel Resolution

Color Gamut Coverage



Low Blue Light

Power Consumption (W, EBL@ 150nits max/ 200nits max) No 2.49 max / 2.98 max



STORAGE AND DRIVES

For storage drives, GB = 1 billion bytes. TB = 1 trillion bytes. Actual formatted capacity is less. Up to 30 GB (for Windows 10 and 11) is reserved for system recovery software.

SSD 128GB 2230 PCIe NVMe	Form Factor	M.2 2230 128GB QLC PCIe NVMe 250,069,680	
NVMe QLC)	Capacity		
	NAND Type		
	Interface		
	Logical Blocks		
	Features	Pyrite	
SSD 1TB 2280 PCIe NVMe	Form Factor	M.2 2280	
QLC (1TB 2280 PCIe NVMe	Capacity	1TB	
QLC 2nd Solid State	NAND Type	QLC	
Drive)	Interface	PCIe NVMe	
	Logical Blocks	2,000,409,264	
	Features	Pyrite	
SSD 256GB 2280 PCIe	Form Factor	M.2 2280	
NVMe QLC (SSD 256GB	Capacity	256GB	
2280 PCIe NVMe QLC)	NAND Type	QLC	
	Interface	PCIe NVMe	
	Logical Blocks	500,118,192	
	Features	Pyrite	
SSD 512GB 2280 PCIe	Form Factor	M.2 2280	
NVMe QLC	Capacity	512GB	
	NAND Type	QLC	
	Interface	PCIe NVMe	
	Logical Blocks	1,000,215,216	
	Features	Pyrite	
SSD 1 TB 2280 PCIe NVMe	Form Factor	M.2 2280	
Value	Capacity	1TB	
	NAND Type	TLC	
	Interface	PCIe NVMe Gen4X4	
	Maximum Sequential Read	3200 MB/s ±20%	
	Maximum Sequential Write	2700 MB/s ±20%	
	Logical Blocks	2,000,409,264	
	Features	Pyrite 2.0; TRIM; L1.2	
1. Available only to HK (Hon	g Kong), TW (Taiwan) and CN (China).		

1. Available only to HK (Hong Kong), TW (Taiwan) and CN (China).



NETWORKING/COMMUNICATIONS

Realtek RTL8852BE 802.11ax 2x2 Wi-Fi + Bluetooth® 5.3 Wireless Card (802.11ax 2x2, supporting gigabit data rate) ¹	Wireless LAN Standards	IEEE 802.11a IEEE 802.11b IEEE 802.11g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax IEEE 802.11d IEEE 802.11e IEEE 802.11h IEEE 802.11h IEEE 802.11i IEEE 802.11k IEEE 802.11r IEEE 802.11v
	Interoperability	Wi-Fi certified modules
	Frequency Band	•802.11b/g/n/ax 2.402 – 2.482 GHz •802.11a/n/ac/ax 4.9 – 4.95 GHz (Japan) 5.15 – 5.25 GHz 5.25 – 5.35 GHz 5.47 – 5.725 GHz 5.825 – 5.850 GHz
	Data Rates	 802.11b: 1, 2, 5.5, 11 Mbps 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps 802.11n: max 300Mbps 802.11ac : max 866.7Mbps 802.11ax : max 1201Mbps
	Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
	Security ²	 IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 certification IEEE 802.11i WAPI
	Network Architecture Models	Ad-hoc (Peer to Peer)
		Infrastructure (Access Point Required)
	Roaming	IEEE 802.11 compliant roaming between access points
	Output Power ³	• 802.11b : +18.5dBm minimum • 802.11g : +17.5dBm minimum



Technical Specifications

	 802.11n HT40(2 802.11n HT20(5 802.11n HT40(5 802.11n HT40(5 802.11ac VHT8 802.11ax HE40 	dBm minimum 2.4GHz) : +15.5dBm minimum 2.4GHz) : +14.5dBm minimum 5GHz) : +15.5dBm minimum 5GHz) : +14.5dBm minimum 0(5GHz) : +11.5dBm minimum (2.4GHz) : +10dBm minimum (5GHz) : +10dBm minimum	
Power Consumption	• Idle mode :50 m	2 W 180 mW (WLAN Associated) W (WLAN unassociated) dby/Modern Standby: 10mW	
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode		
Receiver Sensitivity ⁴	802.11b, 1Mbps : -93.5dBm maximum 802.11b, 11Mbps : -84dBm maximum 802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum 802.11n, MCS07 : -67dBm maximum 802.11n, MCS15 : -64dBm maximum 802.11ac, MCS0 : -84dBm maximum 802.11ac, MCS9 : -59dBm maximum •802.11ax, MCS11(HE40): -57dBm maximum •802.11ax, MCS11(HE80): -54dBm maximum		
Antenna type	enclosure	ntenna with spatial diversity, mounted in the display	
	support WLAN MI	ual band 2.4/5 GHz antennas are provided to the card to MO communications and Bluetooth communications	
Form Factor	PCI-Express M.2 MiniCard		
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm		
Weight	1. Type 2230 : 2.8g 2. Type 126: 1.3g		
Operating Voltage	3.3v +/- 9%		
Temperature	Operating	14° to 158° F (–10° to 70° C)	
	Non-operating	–40° to 176° F (–40° to 80° C)	
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)	
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)	
LED Activity	LED Amber – Radio OFF; LED OFF – Radio ON		
ith Bluetooth 4.0/4.1/4.2/5.0)/5.1/5.2/5.3 Wire	less Card	

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card

Bluetooth Specification 4.0/4.1/4.2/5.0/5.1 Compliant/5.2 Compliant/5.3 Compliant



Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Signaling Data Rate	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

1. Wi-Fi 6 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 (802.11ax) is backwards compatible with prior 802.11 specs.

2. Check latest software/driver release for updates on supported security features.

3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).

Realtek RTL8852BE-VS	Wireless LAN Standards	IEEE 802.11a
802.11ax 1x1 Wi-Fi 6+		IEEE 802.11b
Bluetooth [®] 5.3 Wireless		IEEE 802.11g
Card (802.11ax 1x1) ¹		IEEE 802.11n
		IEEE 802.11ac
		IEEE 802.11ax
		IEEE 802.11d
		IEEE 802.11e
		IEEE 802.11h
		IEEE 802.11i
		IEEE 802.11k
	Interoperability	Wi-Fi certified modules
	Frequency Band	•802.11b/g/n/ax
		2.402 – 2.482 GHz
		•802.11a/n/ac/ax
		4.9 – 4.95 GHz (Japan)
		5.15 – 5.25 GHz
		5.25 – 5.35 GHz
		5.47 – 5.725 GHz
		5.825 – 5.850 GHz
	Data Rates	• 802.11b: 1, 2, 5.5, 11 Mbps
		• 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
		• 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps
		• 802.11n: max 150Mbps



	• 802.11ac : max 433Mbps • 802.11ax : max 600Mbps
Modulation	Direct Sequence Spread Spectrum BPSK, QPSK, CCK, 16-QAM, 64-QAM, 256-QAM, 1024QAM
Security ²	 IEEE and WiFi certified 64 / 128 bit WEP encryption for a/b/g mode only AES-CCMP: 128 bit in hardware 802.1x authentication WPA, WPA2: 802.1x. WPA-PSK, WPA2-PSK, TKIP, and AES. WPA2 certification WPA3 certification IEEE 802.11i WAPI EAP
Network Architecture Models	Ad-hoc (Peer to Peer)
	Infrastructure (Access Point Required)
Roaming	IEEE 802.11 compliant roaming between access points
Output Power ³	 802.11b : +17dBm minimum 802.11g : +16dBm minimum 802.11a : +17dBm minimum 802.11n HT20(2.4GHz) : +14dBm minimum
	• 802.11n HT40(2.4GHz) : +13dBm minimum • 802.11n HT20(5GHz) : +14dBm minimum
	• 802.11n HT40(5GHz) : +13dBm minimum
	• 802.11ac VHT80(5GHz) : +10dBm minimum
	• 802.11ax HE40(2.4GHz) : +12dBm minimum • 802.11ax HE80(5GHz) : +10dBm minimum
Power Consumption	• Transmit mode :2.5 W • Receive mode :2 W
	• Idle mode (PSP) 180 mW (WLAN Associated)
	• Idle mode :50 mW (WLAN unassociated)
	 Connected Standby/Modern Standby: 10mW Radio disabled: 8 mW
Power Management	ACPI and PCI Express compliant power management 802.11 compliant power saving mode
Receiver Sensitivity ⁴	802.11b, 1Mbps : -93.5dBm maximum
	802.11b, 11Mbps : -84dBm maximum
	802.11a/g, 6Mbps : -86dBm maximum 802.11a/g, 54Mbps : -72dBm maximum
	802.11n, MCS07 : -67dBm maximum
	802.11n, MCS15 : -64dBm maximum
	802.11ac, MCS0 : -84dBm maximum
	802.11ac, MCS9 : -59dBm maximum •802.11ax, MCS11(HE40): -57dBm maximum
	•802.11ax, MCS11(HE80): -54dBm maximum



Form Factor	Two embedded dual band 2.4/5 GHz antennas are provided to the card to support WLAN MIMO communications and Bluetooth communications PCI-Express M.2 MiniCard		
Dimensions	1. Type 2230 : 2.3 x 22.0 x 30.0 mm 2. Type 1216: 1.67 x 12.0 x 16.0 mm		
Weight	1. Type 2230 : 2.8g 2. Type 126: 1.3g		
Operating Voltage	3.3v +/- 9%		
Temperature	Operating Non-operating	14° to 158° F (–10° to 70° C) –40° to 176° F (–40° to 80° C)	
Humidity	Operating Non-operating	10% to 90% (non-condensing) 5% to 95% (non-condensing)	
Altitude	Operating Non-operating	0 to 10,000 ft (3,048 m) 0 to 50,000 ft (15,240 m)	
LED Activity	LED Amber – Radio OFF; LED OFF – Radio ON		

HP Integrated Module with Bluetooth 4.0/4.1/4.2/5.0/5.1/5.2/5.3 Wireless Card

Bluetooth Specification	4.0/4.1/4.2/5.0/5.1 Compliant/5.2 Compliant/5.3 Compliant
Frequency Band	2402 to 2480 MHz
Number of Available Channels	Legacy : 0~79 (1 MHz/CH) BLE : 0~39 (2 MHz/CH)
Data Rates and Throughput	Legacy : 3 Mbps data rate; throughput up to 2.17 Mbps BLE : 1 Mbps data rate; throughput up to 0.2 Mbps Legacy : Synchronous Connection Oriented links up to 3, 64 kbps, voice channels Legacy : Asynchronous Connection Less links 2178.1 kbps/177.1 kbps asymmetric (3-DH5) or 864 kbps symmetric (3-EV5)
Transmit Power	The Bluetooth component shall operate as a Class II Bluetooth device with a maximum transmit power of + 4 dBm for BR and EDR.

1. Wi-Fi 6 is designed to support gigabit data rate when transferring files between two devices connected to the same router. Requires a wireless router, sold separately, that supports 80MHz and higher channels.

Wireless access point and Internet service required and sold separately. Availability of public wireless access points limited. Wi-Fi 6 (802.11ax) is backwards compatible with prior 802.11 specs.

2. Check latest software/driver release for updates on supported security features.

3. The FCC has declared as of September 1, 2014 products that utilize passive scanning on channel 12/13 and are capable of transmitting must fully comply with requirements of 15.247 or otherwise disable those channels.

4. Receiver sensitivity is measured at a packet error rate of 8% for 802.11b (CKK modulation) and a packet error rate of 10% for 802.11a/g (OFDM modulation).



POWER

1. Actual battery Watt-hours (Wh) will vary from design capacity. Battery capacity will naturally decrease with shelf life, time, usage, environment, temperature, system configuration, loaded apps, features, power management settings and other factors

HP 45W Smart AC adapter	Dimensions (H x W x D)	3.74 x 1.772 x 1.043 in (9.	5x4 5x2 65cm)	
	Weight	0.44 lb (200 g) max (Not including power cord. Power cord varies by country.)		
	Input	100-240Vac		
		Input Efficiency	87.74 % at 115 Vac and 88.4 % at 230Vac	
		Input frequency range	47-63 Hz	
		Input AC current	Max. 1.4 A at 90 Vac	
	Output	Output power	45W	
		DC output	19.5V	
		Hold-up time	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input	
		Output current limit	< 8.0A	
	Connector	4.5mm Barrel Type		
	Environmental Design	Operating temperature	32ºF to 95ºF (0ºto 35ºC)	
		Non-operating (storage) temperature	-4°F to 185°F (-20°to 85°C)	
		Altitude	0 to 16,400 ft (0 to 5000m)	
		Humidity	20% to 95%	
		Storage Humidity	10% to 95%	
	EMI and Safety Certifications	Worldwide safety standar EN62368-1:2014+A11, UL Agency approvals - C-UL-I Class B, CISPR32 Class B, C and K-MEPS, NOM-001 an	with LVD and EMC directives ds - IEC60950-1 and IEC62368-1 : 2018, .62368-1 JS, TUV/GS, TUV/PSE, EN55032 Class B, FCC CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) d 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, .ia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC	
65W EM Adapter	Dimensions (H x W x D)	4.016 x 2.165 x 1.181 in (1	10.2x5.5x3cm)	
	Weight	0.58 lb (265 g) max (Not including power cord	. Power cord varies by country.)	
	Input	100-240Vac		
		Input Efficiency	88 % at 115 Vac and 89 % at 230Vac	
		Input frequency range	47-63 Hz	
		Input AC current	Max. 1.7 A at 90 Vac	
	Output	Output power	65W	
		DC output	19.5V	
		Hold-up time	100% load 5ms at 115 Vac input/80% load 10ms at 115 Vac input	
		Output current limit	< 11.0A	



	Connector	4.5mm Barrel Type		
	Environmental Design	Operating temperature	32°F to 95°F (0°to 35°C)	
		Non-operating (storage) temperature	-4°F to 185°F (-20°to 85°C)	
		Altitude	0 to 16,400 ft (0 to 5000m)	
		Humidity	20% to 95%	
		Storage Humidity	10% to 95%	
	EMI and Safety Certifications	CE Mark - full compliance with LVD and EMC directives Worldwide safety standards - IEC60950-1 and IEC62368-1 : 2018, EN62368-1:2014+A11, UL62368-1 Agency approvals - C-UL-US, TUV/GS, TUV/PSE, EN55032 Class B, FCC Class B, CISPR32 Class B, CCC and CECP, CU(EAC), EAEU, KCC(Safety+EMC) and K-MEPS, NOM-001 and 029 NYCE, NRcan, NRCS, ISC, SEC, PSB, Argentina S-mark, Australia GEMS and RCM, BIS, BSMI, UAE, UKCA DoC		
HP 3-cell Long Life Li-Ion	Weight	0.185 kg (0.407 lb)		
(41 Wh) ¹	Cells/Type	3cell Lithium-Ion Polymer cell / 515974		
	Energy	Voltage	11.25V	
		Amp-hour capacity	3.648Ah	
		Watt-hour capacity ¹	41.04Wh	
	Temperature	Operating (Charging)	32° to 113° F (0° to 45° C)	
		Operating (Discharging)	14° to 122° F (-10° to 60° C)	
		Optional Travel Battery Available	Νο	



AUDIO

HD Stereo Codec	Realtek ALC3247
Audio I/O Ports	One Headset Combo-Jack connector support CTIA spec.
Internal Speaker Amplifier	2W class D amplifier from ALC3247 for internal speaker only. External speaker must be powered.
Multi-streaming Capable	Playback multi-streaming can be enabled in the audio control panel to allow independent audio streams to be sent to/from the Combo jack or integrated speaker.
Sampling	Independent sampling rates for DAC's and ADC's; supports resolutions from 16 to 24-bit; 44.1 kHz to 48 kHz for DAC and ADC.
Wavetable Syntheses	Yes - Uses OS soft wavetable
Analog Audio	Yes
# of Channels on Line-Out	0
Internal Speaker	Yes

FINGERPRINT READER

Sensor vendor	ELAN EFSA80SW
Sensor type	Capacitive
DPI resolution	508 DPI
Scan area	80 x 80 pixels
False Rejection Rate	FRR=≤ 3%
False Acceptance Rate	< 1:100K
Mobile Voltage Operation	3.0V to 3.6V
Operating Temperature	-4°F ~ 176°F (-20°C ~ 80°C)
Current Consumption	50mA Peak
Image	
Low Latency Wait For	300uA
Finger	
Capture Rate	50 frame/ sec
ESD Resistance	IEC 61000-4-2 4B (+15KV)
Detection Matrix	508 DPI / 4 mm x 4mm



ENVIRONMENTAL DATA

Eco-Label Certifications & declarations	 This product has received or is in the process of being certified to the following approvals and may be labeled with one or more of these marks: IT ECO declaration US ENERGY STAR[®] US Federal Energy Management Program (FEMP) EPEAT^a Gold registered in the United States. See http://www.epeat.net for registration status in your country. China Energy Conservation Program (CECP) China State Environmental Protection Administration (SEPA) Taiwan Green Mark Korea Eco-label Japan PC Green label* 			
Sustainable Impact Specifications	 Product Carbon Footprint (hp.com) Ocean-bound plastic in speaker 20% post-consumer recycled plastic 20% recycled metal Low halogen Outside Box and corrugated cushions are 100% sustainably sourced and recyclable Molded Paper Pulp Cushion inside box is 100% sustainably sourced and recyclable. Bulk packaging available 			
System Configuration	The configuration used for the Energy Consumption and Declared Noise Emissions data for the Notebook model is based on a "Typically Configured Notebook".			
Energy Consumption (in accordance with US ENERGY STAR® test				
method) Normal Operation (Sort idle)	115VAC, 60Hz 5.136 W	230VAC, 50Hz 5.088 W	100VAC, 50Hz 5.028 W	
Normal Operation (Long dle)	0.564 W	0.576 W	0.552 W	
Sleep	0.564 W	0.576 W	0.552 W	
Off	0.168 W	0.204 W	0.156 W	
	model family. HP compute applicable U.S. Environmer computers. If a model fam energy efficiency data liste	rs marked with the ENERGY ntal Protection Agency (EPA ily does not offer ENERGY S	compliant product if offered within the STAR® Logo are compliant with the ENERGY STAR® specifications for TAR® compliant configurations, then ed PC featuring a hard disk drive, a high perating system.	
	115VAC, 60Hz	230VAC, 50Hz	100VAC, 50Hz	
Heat Dissipation* Normal Operation (Short dle)	115VAC, 60Hz 17.6 BTU/hr	230VAC, 50Hz 17.4 BTU/hr	100VAC, 50Hz 17.2 BTU/hr	
Normal Operation (Short dle) Normal Operation (Long	17.6 BTU/hr	17.4 BTU/hr	17.2 BTU/hr	
Normal Operation (Short				



Declared Noise Emissions		Sound Power	Sound Pr	essure
(in accordance with		(L _{WAd} , bels)	(L _{pAm} , decibels)	
ISO 7779 and ISO 9296)				
Typically Configured – Idle		2.4	16.1	
Fixed Disk – Random writes		2.4	16.	
Optical Drive – Sequential reads		N/A	N//	4
Longevity and Upgrading	This product	can be upgraded, possibly e	xtending its useful life by seve	ral years. Upgradeable
			n the Spare parts are available	throughout the warranty
		for up to "5" years after the		
Additional Information	dire	ctive - 2011/65/EC.	th the Restrictions of Hazardou omply with the Waste Electrica	
		pment (WEEE) Directive – 20		
		product is in compliance wi king Water and Toxic Enforc	th California Proposition 65 (St ement Act of 1986).	ate of California; Safe
		product is in compliance wit v.epeat.net	th the IEEE 1680 (EPEAT) stand	lard at the Gold level, see
		tics parts weighing over 25 043.	grams used in the product are	marked per ISO11469 and
	• This	product is 96.8% recycle-at	ole when properly disposed of	at end of life.
Packaging Materials	External:	PAPER/Corrugated		245 g
		PAPER/Paperboard		50 g
		PAPER/Molded Pulp		56 g
	Internal:	PLASTIC/Polyethylene lov	v density - LDPE	10 g
	The plastic p	backaging material contains	at least 100.0% recycled cont	ent.
			als contains at least 35.6% rec	
RoHS Compliance	HP Inc. complies fully with materials regulations. We were among the first companies to extend the restrictions in the European Union (EU) Restriction of Hazardous Substances (RoHS) Directiv to our products worldwide through the HP GSE. HP has contributed to the development of relate legislation in Europe, as well as China, India, and Vietnam.			bstances (RoHS) Directive
	We believe the RoHS directive and similar laws play an important role in promoting industry-wide elimination of substances of concern. We have supported the inclusion of additional substances—including PVC, BFRs, and certain phthalates—in future RoHS legislation that pertains to electrical and electronics products.			
	We met our voluntary objective to achieve worldwide compliance with the new EU RoHS requirements for virtually all relevant products by July 2013, and we will continue to extend the scope of the commitment to include further restricted substances as regulations continue to evolve.			ill continue to extend the
	To obtain a c	opy of the HP RoHS Complia	nce Statement, see HP RoHS p	oosition statement.
Material Usage	This product does not contain any of the following substances in excess of regulatory limits (refer to the HP General Specification for the Environment at http://www.hp.com/hpinfo/globalcitizenship/environment/supplychain/gen_specifications.ht):			
	Cert Cert Cadi Chlo Chlo	Chlorinated Hydrocarbons		



	 Benzyl butyl phthalate (BBP) Dibutyl phthalate (DBP) Diisobutyl phthalate (DIBP) Formaldehyde Halogenated Diphenyl Methanes Lead carbonates and sulfates Lead and Lead compounds Mercuric Oxide Batteries Nickel – finishes must not be used on the external surface designed to be frequently handled or carried by the user. Ozone Depleting Substances Polybrominated Biphenyl Ethers (PBBEs) Polybrominated Biphenyl Oxides (PBBOS) Polybrominated Biphenyl (PCB) Polychlorinated Terphenyls (PCT) Polychlorinated Terphenyls (PCT) Polyvinyl Chloride (PVC) – except for wires and cables, and certain retail packaging has been voluntarily removed from most applications. Radioactive Substances Tributyl Tin (TBT), Triphenyl Tin (TPT), Tributyl Tin Oxide (TBTO)
Packaging Usage	 HP follows these guidelines to decrease the environmental impact of product packaging: Eliminate the use of heavy metals such as lead, chromium, mercury and cadmium in packaging materials. Eliminate the use of ozone-depleting substances (ODS) in packaging materials. Design packaging materials for ease of disassembly. Maximize the use of post-consumer recycled content materials in packaging materials. Use readily recyclable packaging materials such as paper and corrugated materials. Reduce size and weight of packages to improve transportation fuel efficiency. Plastic packaging materials are marked according to ISO 11469 and DIN 6120 standards.
End-of-life Management and Recycling	 HP offers end-of-life HP product return and recycling programs in many geographic areas. To recycle your product, please go to: http://www.hp.com/go/reuse-recycle or contact your nearest HP sales office. Products returned to HP will be recycled, recovered or disposed of in a responsible manner. The EU WEEE directive (2002/95/EC) requires manufacturers to provide treatment information for each product type for use by treatment facilities. This information (product disassembly instructions) is posted on the Hewlett Packard web site at: http://www.hp.com/go/recyclers. These instructions may be used by recyclers and other WEEE treatment facilities as well as HP OEM customers who integrate and re-sell HP equipment.
HP, Inc. Corporate Environmental Information	For more information about HP's commitment to the environment: Global Citizenship Report http://www.hp.com/hpinfo/globalcitizenship/gcreport/index.html Eco-label certifications http://www8.hp.com/us/en/hp-information/environment/ecolabels.html ISO 14001 certificates: http://h20195.www2.hp.com/V2/GetDocument.aspx?docname=c04755842 and http://www.hp.com/hpinfo/globalcitizenship/environment/pdf/cert.pdf
footnotes	 Percentage of ocean-bound plastic contained in each component varies by product Recycled plastic content percentage is based on the definition set in the IEEE 1680.1-2018 standard.



•	 External power supplies, WWAN modules, power cords, cables and peripherals excluded. 100% outer box packaging and corrugated cushions made from sustainably sourced certified and recycled fibers. Fiber cushions made from 100% recycled wood fiber and organic materials. Plastic cushions are made from >90% recycled plastic. Recycled metal is expressed as a percentage of the total weight of the metal according to ISO 14021 definitions for metal parts over 25 grams.
---	---

COUNTRY OF ORIGIN

China



Options and Accessories (Sold separately and availability may vary by country)

Туре	Description	Part Number
Audio	HP Wired USB-A Stereo Headset	428K6AA
	HP Wired 3.5mm Stereo Headset	428K7AA
Cases	HP 115 15.6 Laptop Backpack	8DV45AA#ACJ
	HP 215 15.6 Laptop Backpack	35L98AA#ACJ
	HP 225 15.6 Laptop Backpack	2P7U6AA#ACJ
	HP 235 15.6 Laptop Backpack	35M00AA#ACJ
	HP 315 15.6 Laptop Backpack	35L97AA#ACJ
	HP Prelude G2 15.6 Backpack	1E7D6AA
	HP Prelude G2 15.6 Top Load	1E7D7AA
	HP Prelude Pro Recycled 15.6 Backpack	1X644AA
	HP Prelude Pro Recycled 15.6 Top Load	1X645AA
	HP Renew Business 15.6 Laptop Bag	3E5F8AA
	HP Renew Business 17.3 Laptop Backpack	3E2U5AA
	HP Renew Business 17.3 Laptop Bag	3E2U6AA
	HP Renew Executive 16 Laptop Backpack	6B8Y1AA
	HP Renew Executive 16 Laptop Bag	6B8Y2AA
	HP Travel 18L 15.6 Iron Gray Laptop Backpack	6H2D9AA
	HP Travel 25L 15.6 Iron Gray Laptop Backpack	6H2D8AA
Adapter	HP USB-C to RJ45 Adapter G2	4Z527AA
	HP USB 3.0 to Gigabit RJ45 Adapter G2	4Z7Z7AA
	HP HDMI to VGA Adapter	H4F02AA
Keyboard/Combo	HP 125 WD USB Keyboard	266C9AA
	HP 320K WD USB Keyboard	9SR37AA
	HP 155 Wired Mouse and Keyboard Combo	5B8COAA#ACJ
	HP 225 Antimicrobial Wired Mouse and Keyboard Combo	286K3AA#AB2
	HP 225 Wired Mouse and Keyboard Combo	286J4AA
	HP 235 Wireless Mouse and Keyboard Combo	1Y4D0AA
	HP Wired Desktop 320MK Mouse and Keyboard	9SR36AA
Mouse	HP 125 USB-A Wired Mouse	265A9AA
	HP 128 USB Laser Wired Mouse	265D9AA
	HP 155 USB-A Wired Mouse	5B8B7AA#ACJ
	HP 320M USB-A Wired Mouse	9VA80AA
	HP USB-A+Bluetooth Travel Bluetooth Mouse	6SP30AA
	HP USB Premium Wireless Mouse	1JR31AA
	HP 435 Bluetooth 5.0 + Wireless 2.4GHz Multi-Device Wireless Mouse	3B4Q5AA



Options and Accessories (Sold separately and availability may vary by country)

Commodity	HP USB DVD-Writer EXT ODD	F2B56AA
Video	HP 325 FHD USB-A Webcam	53X27AA



Change Log

Date of change:	Version History:		Description of change:
March 21, 2023	V1 to V2	Updated	Call out in Overview section
March 30, 2023	V2 to V3	Updated	Ports and Slots section
April 19, 2023	V3 to V4	Updated	At a Glance section
May 18, 2023	V4 to V5	Updated	Storage and Drives section
August 1, 2023	V5 to V6	Added	Environmental Data
October 24, 2023	V6 to V7	Added	AMD Athlon™ Silver 7120U Processor
April 24, 2024	V7 to V8	Updated	Memory Section
August 9, 2024	V8 to V9	Updated	Weights & Dimensions Section

© Copyright 2024 HP Development Company, L.P. The information contained herein is subject to change without notice. The only warranties for HP products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. HP shall not be liable for technical or editorial errors or omissions contained herein.

AMD and Radeon are trademarks of Advanced Micro Devices, Inc. Bluetooth is a trademark owned by its proprietor and used by HP Inc. under license. USB Type-C[®] and USB-C[®] are registered trademarks of USB Implementers Forum. ENERGY STAR is a registered trademark of the U.S. Environmental Protection Agency. All other trademarks are the property of their respective owners.

